

Small bar mounting point										Large bar mounting point																
327P4/327P5X	327PT55	436LI/536LI XP®	T536LI XP®	317 Electric/321 Electric	T425	T435	T540 XP®	135/135 e-series	435/435 e-series/440/440 e-series	445/445 e-series/450/450 e-series/543 XP®	545/550 XP®	455 Rancher/455 e-series Rancher	460 Rancher	555/560 XP®	562 XP®	365/372 XP®	570/576 XP®	390 XP®*/395 XP®	3120 XP®	Bar length inches / cm	Chain pitch inches	Gauge inches / cm	Product number	Drive links	Type	Product number
LAMINATED BAR WITH NOSE WHEEL																										
●	●	●																		10/25	3/8 mini	.043/1.1	501 95 95-40	40	H38 Low Vib	581 80 79-40
●	●	●																		12/30	3/8 mini	.043/1.1	501 95 95-45	45	H38 Low Vib	581 80 79-45
	●	●																		14/35	3/8 mini	.043/1.1	501 95 95-52	52	H38 Low Vib	581 80 79-52
●				●																10/25	3/8 mini	.050/1.3	505 89 16-40	40	H37 Low Vib	576 93 65-40
●				●	●	●														12/30	3/8 mini	.050/1.3	501 95 92-45	45	H37 Low Vib	576 93 65-45
				●	●	●	●													14/35	3/8 mini	.050/1.3	501 95 92-52	52	H37 Low Vib	576 93 65-52
				●	●	●	●													16/40	3/8 mini	.050/1.3	501 95 92-56	56	H37 Low Vib	576 93 65-56
								●	●	●	●	●	●	●						13/33	.325	.050/1.3	508 92 61-56	56	H30 Low Vib	501 84 06-56
								●	●	●	●	●	●	●						15/38	.325	.050/1.3	508 92 61-64	64	H30 Low Vib	501 84 06-64
								●	●	●	●	●	●	●						16/40	.325	.050/1.3	508 92 61-66	66	H30 Low Vib	501 84 06-66
								●	●	●	●	●	●	●						18/45	.325	.050/1.3	508 92 61-72	72	H30 Low Vib	501 84 06-72
									●	●	●	●	●	●						20/50	.325	.050/1.3	508 92 61-80	80	H30 Low Vib	501 84 06-80
									●	●	●	●	●	●						13/33	.325	.058/1.5	508 91 21-56	56	H25 Low Vib	501 84 04-56
									●	●	●	●	●	●						15/38	.325	.058/1.5	508 91 21-64	64	H25 Low Vib	501 84 04-64
									●	●	●	●	●	●						16/40	.325	.058/1.5	508 91 21-66	66	H25 Low Vib	501 84 04-66
									●	●	●	●	●	●						18/45	.325	.058/1.5	508 91 21-72	72	H25 Low Vib	501 84 04-72
										●	●	●	●	●						20/50	.325	.058/1.5	508 91 21-80	80	H25 Low Vib	501 84 04-80
										●	●	●	●	●						15/38	3/8	.058/1.5	508 91 41-56	56	H42 Low Vib	501 84 14-56
										●	●	●	●	●						16/40	3/8	.058/1.5	508 91 41-60	60	H42 Low Vib	501 84 14-60
										●	●	●	●	●						18/45	3/8	.058/1.5	508 91 41-68	68	H42 Low Vib	501 84 14-68
										●	●	●	●	●						20/50	3/8	.058/1.5	510 15 35-72	72	H42 Low Vib	501 84 14-72
											●	●	●	●	●					15/38	3/8	.058/1.5	508 91 31-56	56	H42 Low Vib	501 84 14-56
											●	●	●	●	●					16/40	3/8	.058/1.5	508 91 31-60	60	H42 Low Vib	501 84 14-60
											●	●	●	●	●					18/45	3/8	.058/1.5	508 91 31-68	68	H42 Low Vib	501 84 14-68
											●	●	●	●	●					20/50	3/8	.058/1.5	544 28 55-72	72	H42 Low Vib	501 84 14-72
LAMINATED BAR WITH NOSE WHEEL, TECHLITE™																										
	●																			12/30	3/8 mini	.043/1.1	578 10 68-45	45	H38 Low Vib	581 80 79-45
	●																			14/35	3/8 mini	.043/1.1	578 10 68-52	52	H38 Low Vib	581 80 79-52
●				●	●	●														12/30	3/8 mini	.050/1.3	576 83 07-45	45	H37 Low Vib	576 93 65-45
				●	●	●	●													14/35	3/8 mini	.050/1.3	576 83 07-52	52	H37 Low Vib	576 93 65-52
				●	●	●	●													16/40	3/8 mini	.050/1.3	576 83 07-56	56	H37 Low Vib	576 93 65-56
LAMINATED BAR WITH REPLACEABLE TIP, TECHLITE™																										
											●	●	●							20/50	3/8	.058/1.5	544 90 25-72	72	H42 Low Vib	501 84 14-72
											●	●	●							28/70	3/8	.058/1.5	544 90 25-92	92	H42 Low Vib	501 84 14-92
SOLID BAR WITH REPLACEABLE TIP																										
											●	●	●							18/45	3/8	.058/1.5	501 95 77-68	68	H42 Low Vib	501 84 14-68
											●	●	●							20/50	3/8	.058/1.5	501 95 77-72	72	H42 Low Vib	501 84 14-72
											●	●	●	●						18/45	3/8	.058/1.5	501 95 69-68	68	H42 Low Vib	501 84 14-68
											●	●	●	●						20/50	3/8	.058/1.5	501 95 69-72	72	H42 Low Vib	501 84 14-72
											●	●	●	●						24/60	3/8	.058/1.5	501 95 69-84	84	H42 Low Vib	501 84 14-84
											●	●	●	●						28/70	3/8	.058/1.5	501 95 69-92	92	H42 Low Vib	501 84 14-92
SOLID BAR																										
				●																10/25	1/4	.050/1.3	505 89 15-60	60	H00	501 84 40-60
●																				10/25	1/4	.050/1.3	575 84 22-58	58	H00	501 84 40-58
●																				12/30	1/4	.050/1.3	575 84 22-64	64	H00	501 84 40-64
											●	●	●	●						18/45	3/8	.058/1.5	501 95 80-68	68	H42 Low Vib	501 84 14-68
											●	●	●	●						20/50	3/8	.058/1.5	501 95 80-72	72	H42 Low Vib	501 84 14-72
											●	●	●	●						24/60	3/8	.058/1.5	501 95 80-84	84	H42 Low Vib	501 84 14-84
											●	●	●	●						28/70	3/8	.058/1.5	501 95 80-92	92	H42 Low Vib	501 84 14-92
											●	●								24/60	.404	.063/1.6	507 47 60-46	76	H64	501 84 31-76
											●	●								28/70	.404	.063/1.6	501 58 96-01	84	H64	501 84 31-84
											●	●								30/75	.404	.063/1.6	501 95 81-92	92	H64	501 84 31-92
											●	●								36/90	.404	.063/1.6	501 95 81-04	104	H64	501 84 31-04
											●	●								42/105	.404	.063/1.6	501 92 18-24	124	H64	501 84 31-24

*Solid bar with .404 chain pitch on 390 XP® is optional on certain markets.